Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-467-4833

Cross Sectional Shape:         Round         Thread Class:         2b 1st end         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.875 inches         Tempurature Rating:         -40.0 degrees fahrenheit single response         Outside Diameter:         1.000 inches         Minimum Inside Bending Radius:         9.825 inches         Connection Style:         Swivel nut, flareless 1st end         End Connection Design:         Straight 1st end         Connection Type:         Thready day Per Inch (tpi):         12 1st end         Burst Test Pressure:         30000.0 pounds per square inch         Maximum Operating Pressure:         3000.0 pounds per square inch         Maximum Operating Pressu	
Thread Class:         2b 1st end         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.875 inches         Tempurature Rating:         +40.0 digrees fahrenheit single response         Outside Diameter:         1.000 inches         Minimum Inside Bending Radius:         9.625 inches         Connection Style:         Swivel nut, flareless 1st end         End Connection Design:         Straight 1st end         Connection Type:         Thready Clay Per Inch (tpi):         12 tet and         Burst Test Pressure:         10000.0 pounds per square inch         Maximum Operating Pressure:         3000.0 pounds per square inch         Marce State of         Enter Covering Environmental Protection:         Abarsion resistant         Inside Surface Condition:         Smooth         Measuring Method And Length:         23.300 inches         Hedia For Which Designed:         Hydraulic fluid single response	Cross Sectional Shape:
2b 1st end         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.875 inches         Temprature Rating:         -40.0 degrees fahrenheit single response         Outside Diameter:         1.000 inches         Minimu Inside Bending Radius:         9.625 inches         Connection Style:         Swivel nut, flareless 1st end         Ed Connection Design:         Straight 1st end         Connection Type:         Thread diremal tube 1st end         Thread of thermal tube 1st end         Thread of thermal tube 1st end         Maximum Operating Pressure:         10000.0 pounds per square inch         Maximum Operating Pressure:         10.100.0 pounds per square inch         Maximum Operating Pressure:         10.20 inches         Maximum Operating Protection:         Abrasion resistant         Inside Surface Condition:         Snoth         Measuring Method And Length:         23.800 inches         Media For Which Designed:         Hydrakif fuid single response         Hydrakif fuid single response         Inside Surface Condition:         23.800 inches	Round
Thread Direction:         Right-hand 1st end         Inside Diameter:         0.875 inches         Tempurature Rating:         -40.0 degrees fahrenheit single response         Outside Diameter:         1.000 inches         Minimum Inside Bending Radius:         9.625 inches         Connection Style:         Swivel nut, flareless 1st end         End Connection Design:         Straight 1st end         Connection Type:         Thread Qup Per Inch (tpl):         12 1st end         Burst Test Pressure:         10000.0 pounds per square inch         Maximum Operating Pressure:         10000.0 pounds per square inch         Maximum Gegrees 1st end         Thread Size:         1.312 inches 1st end         Straight 1st end         Straight 1st end         Maximum Operating Pressure:         10000.0 pounds per square inch         Maximum Operating Pressure:         12.0 degrees 1st end         Duter Covering Environmental Protection:         Abrasion resistant         Inside Surface Condition:         Smooth         Meeta For Which Designed:         Hydrawifc fuid single response	Thread Class:
Right-hand 1st end         Inside Diameter:         0.875 inches         Tempurature Rating:         -40.0 degrees fahrenheit single response         Outside Diameter:         1.000 inches         Minimum Inside Bending Radius:         9.625 inches         Connection Style:         Swivel nut, flareless 1st end         End Connection Design:         Straight 1st end         Onnection Type:         Threaded internal tube 1st end         Thready Qty Per Inch (tpl):         12 1st end         Burst Test Pressure:         10000.0 pounds per square inch         Maximum Operating Pressure:         10000.0 pounds per square inch         Maximum Operating Pressure:         1020.0 pounds per square inch         Maximum Operating Pressure:         10200.0 pounds per square inch         Maximum Operating Protection:         Apresi	2b 1st end
Inside Diameter:         0.875 inches         Tempurature Rating:         -40.0 degrees fahrenheit single response         Outside Diameter:         1.000 inches         Minimum Inside Bending Radius:         9.625 inches         Connection Style:         Swivel nut, flareless 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Thready Qty Per Inch (tpl):         12 st end         Burst Test Pressure:         10000.0 pounds per square inch         Maximum Operating Pressure:         10000.0 pounds per square inch         Maximum Operating Pressure:         12.1 inches 1st end         Duter Covering Environmental Protection:         Abrasion resistant         Inside Surface Condition:         Snooth         Measuring Method And Length:         23.800 inches         Meale For Which Designed:         Hydraulic fluid single response         Thread Series Designator:         Un 1st end	Thread Direction:
NaTs inches         Tempurature Rating:         -40.0 degrees fahrenheit single response         Outside Diameter:         1.000 inches         Minimum Inside Bending Radius:         9.625 inches         Connection Style:         Swivel nut, flareless 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Threaded internal tube 1st end         Thready Oty Per Inch (tpi):         12 1st end         Burst Test Pressure:         3000.0 pounds per square inch         Maximum Operating Pressure:         3000.0 pounds per square inch         Thread Size:         1.312 inches 1st end         Statage:         12.0 degrees 1st end         Outer Covering Environmental Protection:         Abrasion resistant         Inside Surface Condition:         Smooth         Measuring Method And Length:         23.800 inches         Heydraulic fluid single response         Thread Series Designator:         Un 1st end         Specification Data:	Right-hand 1st end
Fempurature Rating:         -40.0 degrees fahrenheit single response         Outside Diameter:         1.000 inches         Minimun Inside Bending Radius:         9.625 inches         Connection Style:         Swivel nut, flareless 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Threaded internal tube 1st end         Burst Test Pressure:         10000.0 pounds per square inch         Maximum Operating Pressure:         3000.0 pounds per square inch         Pareed Size:         1.312 inches 1st end         Statage:         12.0 degrees 1st end         Statage:         12.0 degrees 1st end         Marianum Operating Pressure:         3000.0 pounds per square inch         Hread Size:         1.312 inches 1st end         Burst Test Pressure:         1.302 inches 1st end         Burst Coordition:         Smoth         Measuring Method And Length:         2.3.800 inches         Heida For Which Designed:         Hydraulic fluid single response         Thread Series Designator: <t< td=""><td>Inside Diameter:</td></t<>	Inside Diameter:
-40.0 degrees fahrenheit single responseOutside Diameter:1.000 inchesMinimun Inside Bending Radius:9.625 inchesConnection Style:Swivel nut, flareless 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endThreaded internal tube 1st endBurst Test Pressure:1000.0 pounds per square inchMaximum Operating Pressure:3000.0 pounds per square inchStat Apple:1.312 inches 1st endSteat Apple:1.32.0 inches 1st endMaximum Operating Pressure:3000.0 pounds per square inchMaximum Operating Pressure:3000.0 pounds per square inchMaximum Operating Pressure:3000.0 pounds per square inchStat Angle:1.312 inches 1st endSeat Angle:1.32.0 inches 1st endOuter Covering Environmental Protection:Abrasion resistantInside Surface Condition:SmoothMeasuring Method And Length:23.800 inchesMedia For Which Designed:Hydraulic fluid single responseThread Series Designator:Un 1st endSpecification Data:	0.875 inches
Outside Diameter:1.000 inchesMinimun Inside Bending Radius:9.625 inchesConnection Style:Swivel nut, flareless 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endThready Gty Per Inch (tpi):12 1st endBurst Test Pressure:10000.0 pounds per square inchMaximum Operating Pressure:1300.0 pounds per square inchStatagle:1.312 inches 1st endSeat Angle:12.0 degrees 1st endOuter Covering Environmental Protection:Abrasion resistantInside Surface Condition:23.800 inchesMedia For Which Designed:Hydraulic fluid single responseThread Size:1.312 inches1.312 inches 1st endOuter Covering Environmental Protection:Abrasion resistantInside Surface Condition:23.800 inchesMedia For Which Designed:Hydraulic fluid single responseThread Series Designator:Un 1st endSpecification Data:	Tempurature Rating:
<ul> <li>1.000 inches</li> <li>Minimun Inside Bending Radius:</li> <li>9.625 inches</li> <li>Connection Style:</li> <li>Swivel nut, flareless 1st end</li> <li>End Connection Design:</li> <li>Straight 1st end</li> <li>Connection Type:</li> <li>Threaded internal tube 1st end</li> <li>Thready Qty Per Inch (tpi):</li> <li>12 1st end</li> <li>Burst Test Pressure:</li> <li>10000.0 pounds per square inch</li> <li>Maximum Operating Pressure:</li> <li>3000.0 pounds per square inch</li> <li>Thread Size:</li> <li>1.312 inches 1st end</li> <li>Seat Angle:</li> <li>12.0 degrees 1st end</li> <li>Duter Covering Environmental Protection:</li> <li>Abrasion resistant</li> <li>Inside Surface Condition:</li> <li>Smooth</li> <li>Measuring Method And Length:</li> <li>23.800 inches</li> <li>Media For Which Designed:</li> <li>Hydraulic fluid single response</li> <li>Thread Size: Site Site Site Site Site Site Site Site</li></ul>	-40.0 degrees fahrenheit single response
Minimum Inside Bending Radius:9.625 inchesConnection Style:Swivel nut, flareless 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endThready Qty Per Inch (tpi):12 1st endBurst Test Pressure:1000.0 pounds per square inchMaximum Operating Pressure:3000.0 pounds per square inchThread Size:1.312 inches 1st endSeat Angle:12.0 degrees 1st endOuter Covering Environmental Protection:Abrasion resistantInside Surface Condition:SmoothMeasuring Method And Length:23.800 inchesHedia For Which Designed:Hydraulic fluid single responseThread Sizeis Designato::Un 1st endSpecification Data:	Outside Diameter:
9.625 inches Connection Style: Swivel nut, flareless 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 13000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch 3000.0 p	1.000 inches
Connection Style:Swivel nut, flareless 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endThready Qty Per Inch (tpi):12 1st endBurst Test Pressure:10000.0 pounds per square inchMaximum Operating Pressure:3000.0 pounds per square inchMaximus Operating Pressure:1312 inches 1st endSeat Angle:12.0 degrees 1st endOuter Covering Environmental Protection:Abrasion resistantInside Surface Condition:23.800 inchesMedia For Which Designed:23.800 inchesMedia For Which Designed:Hydraulic fluid single responseThread Series Designator:Un 1st endSpecification Data:	Minimum Inside Bending Radius:
Swivel nut, flareless 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endThready Qty Per Inch (tpi):12 1st endBurst Test Pressure:10000.0 pounds per square inchMaximum Operating Pressure:3000.0 pounds per square inchThread Size:1.312 inches 1st endSeat Angle:12.0 degrees 1st endOuter Covering Environmental Protection:Abrasion resistantInside Surface Condition:SmoothMeasuring Method And Length:23.800 inchesMedia For Which Designed:Hydraulic fluid single responseThread Size:Un 1st endSpecification Data:	9.625 inches
End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         10000.0 pounds per square inch         Maximum Operating Pressure:         3000.0 pounds per square inch         Thread Size:         1.312 inches 1st end         Seat Angle:         12.0 degrees 1st end         Outer Covering Environmental Protection:         Abrasion resistant         Inside Surface Condition:         Smooth         Measuring Method And Length:         23.800 inches         Hydraulic fluid single response         Thread Series Designator:         Un 1st end         Specification Data:	Connection Style:
Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 10000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 12.0 degrees 1st end Seat Angle: 12.0 degrees 1st end Outer Covering Environmental Protection: Abrasion resistant Inside Surface Condition: Smooth Measuring Method And Length: 23.800 inches Media For Which Designed: Hydraulic fluid single response Thread Series Designator: Un 1st end Specification Data:	Swivel nut, flareless 1st end
Connection Type:Threaded internal tube 1st endThready Qty Per Inch (tpi):12 1st endBurst Test Pressure:10000.0 pounds per square inchMaximum Operating Pressure:3000.0 pounds per square inchThread Size:1.312 inches 1st endSeat Angle:12.0 degrees 1st endOuter Covering Environmental Protection:Abrasion resistantInside Surface Condition:SmoothMeasuring Method And Length:23.800 inchesHydraulic fluid single responseThread Series Designator:Un 1st endSpecification Data:	End Connection Design:
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 10000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 12.0 degrees 1st end Outer Covering Environmental Protection: Abrasion resistant Inside Surface Condition: Smooth Measuring Method And Length: 23.800 inches Media For Which Designed: Hydraulic fluid single response Thread Series Designator: Un 1st end Specification Data:	Straight 1st end
Thready Qty Per Inch (tpi):12 1st endBurst Test Pressure:10000.0 pounds per square inchMaximum Operating Pressure:3000.0 pounds per square inchThread Size:1.312 inches 1st endSeat Angle:12.0 degrees 1st endOuter Covering Environmental Protection:Abrasion resistantInside Surface Condition:SmoothMeasuring Method And Length:23.800 inchesHydraulic fluid single responseThread Series Designator:Un 1st endSpecification Data:	Connection Type:
12 1st end Burst Test Pressure: 10000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 12.0 degrees 1st end Outer Covering Environmental Protection: Abrasion resistant Inside Surface Condition: Smooth Measuring Method And Length: 23.800 inches Media For Which Designed: Hydraulic fluid single response Thread Series Designator: Un 1st end Specification Data:	Threaded internal tube 1st end
Burst Test Pressure: 10000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 1.312 inches 1st end Seat Angle: 12.0 degrees 1st end Outer Covering Environmental Protection: Abrasion resistant Inside Surface Condition: Smooth Measuring Method And Length: 23.800 inches Media For Which Designed: Hydraulic fluid single response Thread Series Designator: Un 1st end Specification Data:	Thready Qty Per Inch (tpi):
<ul> <li>10000.0 pounds per square inch</li> <li>Maximum Operating Pressure:</li> <li>3000.0 pounds per square inch</li> <li>Thread Size:</li> <li>1.312 inches 1st end</li> <li>Seat Angle:</li> <li>12.0 degrees 1st end</li> <li>Outer Covering Environmental Protection:</li> <li>Abrasion resistant</li> <li>Inside Surface Condition:</li> <li>Smooth</li> <li>Measuring Method And Length:</li> <li>23.800 inches</li> <li>Media For Which Designed:</li> <li>Hydraulic fluid single response</li> <li>Thread Series Designator:</li> <li>Un 1st end</li> <li>Specification Data:</li> </ul>	12 1st end
Maximum Operating Pressure:3000.0 pounds per square inchSoure Size:1.312 inches 1st endSeat Angle:12.0 degrees 1st endOuter Covering Environmental Protection:Abrasion resistantInside Surface Condition:SmoothMeasuring Method And Length:23.800 inchesHydraulic fluid single responseThread Series Designato:Un 1st endSpecification Data:	Burst Test Pressure:
3000.0 pounds per square inchThread Size:1.312 inches 1st endSeat Angle:12.0 degrees 1st endOuter Covering Environmental Protection:Abrasion resistantInside Surface Condition:SmoothMeasuring Method And Length:23.800 inchesMedia For Which Designed:Hydraulic fluid single responseThread Series Designator:Un 1st endSpecification Data:	10000.0 pounds per square inch
Thread Size:1.312 inches 1st endSeat Angle:12.0 degrees 1st endOuter Covering Environmental Protection:Abrasion resistantInside Surface Condition:SmoothMeasuring Method And Length:23.800 inchesMedia For Which Designed:Hydraulic fluid single responseThread Series Designator:Un 1st endSpecification Data:	Maximum Operating Pressure:
<ul> <li>1.312 inches 1st end</li> <li>Seat Angle:</li> <li>12.0 degrees 1st end</li> <li>Outer Covering Environmental Protection:</li> <li>Abrasion resistant</li> <li>Inside Surface Condition:</li> <li>Smooth</li> <li>Measuring Method And Length:</li> <li>23.800 inches</li> <li>Media For Which Designed:</li> <li>Hydraulic fluid single response</li> <li>Thread Series Designator:</li> <li>Un 1st end</li> <li>Specification Data:</li> </ul>	3000.0 pounds per square inch
Seat Angle: 12.0 degrees 1st end Outer Covering Environmental Protection: Abrasion resistant Inside Surface Condition: Smooth Measuring Method And Length: 23.800 inches Media For Which Designed: Hydraulic fluid single response Thread Series Designator: Un 1st end Specification Data:	Thread Size:
12.0 degrees 1st end Outer Covering Environmental Protection: Abrasion resistant Inside Surface Condition: Smooth Measuring Method And Length: 23.800 inches Media For Which Designed: Hydraulic fluid single response Thread Series Designator: Un 1st end Specification Data:	1.312 inches 1st end
Outer Covering Environmental Protection:Abrasion resistantInside Surface Condition:SmoothMeasuring Method And Length:23.800 inchesMedia For Which Designed:Hydraulic fluid single responseThread Series Designator:Un 1st endSpecification Data:	Seat Angle:
Abrasion resistant Inside Surface Condition: Smooth Measuring Method And Length: 23.800 inches Media For Which Designed: Hydraulic fluid single response Thread Series Designator: Un 1st end Specification Data:	12.0 degrees 1st end
Inside Surface Condition:SmoothMeasuring Method And Length:23.800 inchesMedia For Which Designed:Hydraulic fluid single responseThread Series Designator:Un 1st endSpecification Data:	Outer Covering Environmental Protection:
Smooth Measuring Method And Length: 23.800 inches Media For Which Designed: Hydraulic fluid single response Thread Series Designator: Un 1st end Specification Data:	Abrasion resistant
Measuring Method And Length:23.800 inchesMedia For Which Designed:Hydraulic fluid single responseThread Series Designator:Un 1st endSpecification Data:	Inside Surface Condition:
23.800 inches Media For Which Designed: Hydraulic fluid single response Thread Series Designator: Un 1st end Specification Data:	Smooth
Media For Which Designed: Hydraulic fluid single response Thread Series Designator: Un 1st end Specification Data:	Measuring Method And Length:
Hydraulic fluid single response Thread Series Designator: Un 1st end Specification Data:	23.800 inches
Thread Series Designator: Un 1st end Specification Data:	Media For Which Designed:
Un 1st end Specification Data:	Hydraulic fluid single response
Specification Data:	Thread Series Designator:
	Un 1st end
	Specification Data:
96906-ms28762 government standard	96906-ms28762 government standard

## NSN 4720-01-467-4833

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0