

View Online at <https://aerobasegroup.com/nsn/4720-01-468-4288>

Cross Sectional Shape:

Round

Thread Class:

2b 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.880 inches

Temperature Rating:

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Outside Diameter:

1.600 inches

Minimum Inside Bending Radius:

9.630 inches

End Application:

5420-01-430-5403, carrier, bridge launching, lscp940001, 19207

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal hose 2nd end

Thread Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

16000.0 pounds per square inch

Maximum Operating Pressure:

4000.0 pounds per square inch

Thread Size:

1.4375 inches 2nd end

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

28.250 inches and 28.750 inches

Product Name:

Hose assembly, polytetrafluoroethylene, high pressure, crimped

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0