

View Online at <https://aerobasegroup.com/nsn/4720-01-468-4288>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 2nd end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.880 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

**Outside Diameter:**

1.600 inches

**Minimum Inside Bending Radius:**

9.630 inches

**End Application:**

5420-01-430-5403, carrier, bridge launching, lscp940001, 19207

**Connection Style:**

Swivel nut, gasket seal 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal hose 2nd end

**Thread Qty Per Inch (tpi):**

12 2nd end

**Burst Test Pressure:**

16000.0 pounds per square inch

**Maximum Operating Pressure:**

4000.0 pounds per square inch

**Thread Size:**

1.4375 inches 2nd end

**Flow Angle:**

90.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

28.250 inches and 28.750 inches

**Product Name:**

Hose assembly, polytetrafluoroethylene, high pressure, crimped

**Media For Which Designed:**

Hydraulic fluid single response

**Thread Series Designator:**

Un 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0