

View Online at <https://aerobasegroup.com/nsn/4720-01-469-6933>

Cross Sectional Shape:

Round

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Outside Diameter:

0.500 inches

Minimum Inside Bending Radius:

1.250 inches

Exterior Color:

Natural

End Application:

3k rowpu

Connection Style:

Swivel nut with compression sleeve 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube all ends

Features Provided:

Reusable end fittings and identical ends

Burst Test Pressure:

1000.0 pounds per square inch single response

Maximum Operating Pressure:

250.0 pounds per square inch single response

Thread Size:

0.750 inches 1st end

Hydrostatic Test Pressure:

500.0 pounds per square inch single response

Outer Covering Environmental Protection:

Abrasion resistant and heat resistant and light resistant and water resistant and cold resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

5.250 inches

Seat Radius:

0.001 inches 1st end

Product Name:

Tubing jumper

Special Features:

Flexible; temp rating: -65 f and 200 f; first end fitting/material: complete fitting, copper alloy; thread series: unef

Material:

Plastic polyamide body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541y0