

View Online at <https://aerobasegroup.com/nsn/4720-01-469-6950>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.750 inches

**Temperature Rating:**

160.0 degrees fahrenheit single response

**Outside Diameter:**

Between 1.156 inches and 1.219 inches

**Minimum Inside Bending Radius:**

9.500 inches

**End Application:**

2500kw module gen

**Connection Style:**

Swivel nut, inverted flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

200.0 pounds per square inch

**Layer Composition And Location:**

1st layer molded polytetrafluoroethylene and 2nd layer braided wire and outer layer molded polytetrafluoroethylene

**Maximum Operating Pressure:**

50.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

37.000 inches

**Special Features:**

Stainless steel fittings may be substituted with all steel fittings

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0