

View Online at <https://aerobasegroup.com/nsn/4720-01-469-7990>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

Between 0.109 inches and 0.141 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

**Outside Diameter:**

Between 0.328 inches and 0.375 inches

**Minimum Inside Bending Radius:**

1.750 inches

**End Application:**

Truck, cargo; nsn 2320-01-447-3891, p/n 87t0071, cage 19207

**Burst Test Pressure:**

2000.0 pounds per square inch single response

**Layer Composition And Location:**

1st layer molded rubber, buna-n err-100

**Maximum Operating Pressure:**

500.0 pounds per square inch single response

**Hydrostatic Test Pressure:**

1000.0 pounds per square inch single response

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

28.000 inches

**Material:**

Rubber butadiene-acrylonitrile class nbr tube

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Test Data Document:**

Z4193-mil-std-810 standard (includes industry or association standards, individual manufactureer standards, etc.). And 81346-astm-d-380 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Specification Data:**

81349-mil-dtl-13444g government specification

**Specification Or Standard:**

1 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A541z0