

View Online at <https://aerobasegroup.com/nsn/4720-01-469-7990>

Cross Sectional Shape:

Round

Inside Diameter:

Between 0.109 inches and 0.141 inches

Tempurature Rating:

-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

Outside Diameter:

Between 0.328 inches and 0.375 inches

Minimum Inside Bending Radius:

1.750 inches

End Application:

Truck, cargo; nsn 2320-01-447-3891, p/n 87t0071, cage 19207

Burst Test Pressure:

2000.0 pounds per square inch single response

Layer Composition And Location:

1st layer molded rubber, buna-n err-100

Maximum Operating Pressure:

500.0 pounds per square inch single response

Hydrostatic Test Pressure:

1000.0 pounds per square inch single response

Inside Surface Condition:

Smooth

Measuring Method And Length:

28.000 inches

Material:

Rubber butadiene-acrylonitrile class nbr tube

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Test Data Document:

Z4193-mil-std-810 standard (includes industry or association standards, individual manufactureer standards, etc.). And 81346-astm-d-380 standard (includes industry or association standards, individual manufactureer standards, etc.).

Specification Data:

81349-mil-dtl-13444g government specification

Specification Or Standard:

1 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541z0