Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-469-9254

Cross Sectiona	Shape:
Round	
Thread Class:	
2b 1st end	
Thread Directio	n:
Right-hand 1st e	nd
Inside Diameter	:
Between 1.125 in	nches and 1.172 inches
Tempurature Ra	iting:
-55.0 degrees fa	hrenheit single response and 300.0 degrees fahrenheit single response
Outside Diamet	er:
Between 1.456 in	nches and 1.518 inches
Minimum Inside	Bending Radius:
4.500 inches	
Hose Or Tubing	Specification/std Data:
Mil-h-13444e, ty	peiii standard (includes industry or association standards, individual manufactureer standards, etc.).
First End Fitting	g Specification/std Data:
Sae j516, table 4	a-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).
Second End Fit	ting Specification/std Data:
Sae j516, table6a	a-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).
End Application	
NSN2-32-001-44	.73
Connection Sty	le:
Swivel nut flare 2	2nd end
End Connection) Design:
Straight 1st end	
End Fitting Con	nponent And Material:
Complete fitting	steel all ends
Fitting Compon	ent And Surface Treatment:
Complete fitting	zinc 1st end
Connection Typ	e:
Threaded interna	Il tube 1st end
Thready Qty Pe	r Inch (tpi):
12 2nd end	
Second End Re	lationship With First End:
Not identical	
Burst Test Pres	sure:
1250.0 pounds p	er square inch
	I Action Capability:
Not included	
Layer Composi	tion And Location:
	rubber, synthetic err-100



Maximum Operating Pressure: 300.0 pounds per square inch **Thread Size:** 1.3125 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 625.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end **Outer Covering Environmental Protection:** Ozone resistant and oil resistant and fuel resistant and mildew resistant **Inside Surface Condition:** Smooth Measuring Method And Length: 1512.0 millimeters and 1538.0 millimeters Second End Swivel Action Capability: Not included **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Un 2nd end **Specification Data:** 81349-mil-h-13444e government specification Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A542a0 Mil-std (military Standard): Mil-h-13444 spec.