

View Online at <https://aerobasegroup.com/nsn/4720-01-469-9258>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.234 inches and 0.266 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

Outside Diameter:

Between 0.469 inches and 0.531 inches

Minimum Inside Bending Radius:

2.250 inches

Exterior Color:

Olive drab

Hose Or Tubing Specification/std Data:

-mil-h-13444e, typei standard (includes industry or association standards, individual manufactureer standards, etc.).

First End Fitting Specification/std Data:

Mil-h-13444e, para3.3.3.1 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Application:

NSN2-32-001-4476

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Fitting Component And Surface Treatment:

Complete fitting zinc 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

20 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

1250.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer rubber impregnated braided fabric err-100

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

0.4375 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

625.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.500 inches and 19.500 inches

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Specification Data:

81349-mil-h-13444e government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13444 spec.