Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-470-3679

Outside Diameter: Between 0.656 inches and 0.719 Minimum Inside Bending Radi 4.000 inches Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Locat	us:
0.250 inches Tempurature Rating: -40.0 degrees fahrenheit and 21 Outside Diameter: Between 0.656 inches and 0.719 Minimum Inside Bending Radi 4.000 inches Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Locat 1st layer molded rubber, synthe	9 inches us:
Tempurature Rating: -40.0 degrees fahrenheit and 21 Outside Diameter: Between 0.656 inches and 0.719 Minimum Inside Bending Radi 4.000 inches Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Locat 1st layer molded rubber, synthe	9 inches us:
-40.0 degrees fahrenheit and 21 Outside Diameter: Between 0.656 inches and 0.719 Minimum Inside Bending Radi 4.000 inches Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Locat 1st layer molded rubber, synthe	9 inches us:
Outside Diameter: Between 0.656 inches and 0.719 Minimum Inside Bending Radi 4.000 inches Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Locat 1st layer molded rubber, synthe	9 inches us:
Between 0.656 inches and 0.719 Minimum Inside Bending Radi 4.000 inches Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Locat 1st layer molded rubber, synthe	us:
Minimum Inside Bending Radi 4.000 inches Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Locat 1st layer molded rubber, synthe	us:
4.000 inches Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Locat 1st layer molded rubber, synthe	
Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Locat 1st layer molded rubber, synthe	
20000.0 pounds per square inch Layer Composition And Locat 1st layer molded rubber, synthe	
Layer Composition And Locat 1st layer molded rubber, synthe	
1st layer molded rubber, synthe	ion
	tic and 2nd layer spirally laid steel wire and outer layer molded rubber, synthetic
maximum operating riessure:	
5000.0 pounds per square inch Inside Surface Condition:	
Smooth	
Measuring Method And Length	n-
28.000 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single resp	
Specification Data:	
81343-j517 professional/industria	al association standard
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A542a0	