

View Online at <https://aerobasegroup.com/nsn/4720-01-472-6231>

Cross Sectional Shape:

Round

Wall Thickness:

0.035 inches

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.455 inches and 0.485 inches

Tempurature Rating:

-67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Outside Diameter:

Between 1.015 inches and 1.406 inches

Minimum Inside Bending Radius:

6.300 inches

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

14 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer molded polytetrafluoroethylene and 2nd layer spirally wrapped corrosion resistant steel fabric and 3rd layer spirally wrapped corrosion resistant steel fabric and 4th layer spirally wrapped corrosion resistant steel fabric and 5th layer spirally wrapped corrosion resistant steel fabric and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3500.0 pounds per square inch

Thread Size:

0.875 inches 1st end

Seat Angle:

24.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

25.375 inches

Special Features:

End swivel 180 degrees

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

FiiG:

A542a0