## NSN 4720-01-473-3625

**Cross Sectional Shape:** 

Thread Direction:
Right-hand 1st end
Inside Diameter:

**Tempurature Rating:** 

**Thread Series Designator:** 

Nptf 1st end

0.250 inches

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-473-3625

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:
Between 0.594 inches and 0.656 inches
Minimum Inside Bending Radius:
4.000 inches
End Application:
2350-01-368-9500
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
11000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
2750.0 pounds per square inch
Thread Size:
0.250 inches 1st end
Hydrostatic Test Pressure:
5500.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and ozone resistant and mildew resistant
Oil resistant and ozone resistant and mildew resistant
Oil resistant and ozone resistant and mildew resistant  Inside Surface Condition:
Oil resistant and ozone resistant and mildew resistant  Inside Surface Condition:  Smooth
Oil resistant and ozone resistant and mildew resistant Inside Surface Condition: Smooth Measuring Method And Length:
Oil resistant and ozone resistant and mildew resistant Inside Surface Condition: Smooth Measuring Method And Length: 65.000 inches
Oil resistant and ozone resistant and mildew resistant Inside Surface Condition: Smooth Measuring Method And Length: 65.000 inches Special Features:

## NSN 4720-01-473-3625

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0