## NSN 4720-01-474-0511

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-474-0511

Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
Between 1.750 inches and 1.875 inches
Minimum Inside Bending Radius:
5.000 inches
Angle Between Rigid Elbow Fittings In Deg:
270.0
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Threaded internal tube 1st end
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
100.0 pounds per square inch
Thread Size:
1.625 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
200.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
14.365 inches working
Special Features:
Pn d3079 stainless material is 316l; specification allows either 316l or 321 stainless steel
Media For Which Designed:

Water, salt single response and fuel/oil, hydrocarbon single response

## NSN 4720-01-474-0511

Nonmetallic Hose Assembly - Page 2 of 2



Thread	<b>Series</b>	Design	nator:
	0000	_00.9.	

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0