## NSN 4720-01-475-6916

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-475-6916

Cross Sectional Shape:
Round
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Minimum Inside Bending Radius:
7.000 inches
End Application:
5420-01-430-5403
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
2000.0 pounds per square inch
Hydrostatic Test Pressure:
4000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant and hydraulic solution resistant and oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
300.000 inches
Special Features:
Assembly consists of hose assembly nsn 4720-00-792-9883 plus quick connect nsn 4730-01-167-1997 with cap nsn 4730-00-270-6302;
2nd end quick connect nsn 4730-01-103-2469 with plug nsn 4730-01-091-8057; marker 10867455 located on center hose
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A542a0