## NSN 4720-01-479-0581

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-479-0581

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 2b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.250 inches   |
| Tempurature Rating:  |
| -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response                                  |
| Outside Diameter:  |
| 0.690 inches   |
| Minimum Inside Bending Radius:   |
| 4.000 inches   |
| Exterior Color:  |
| Black  |
| End Application:   |
| GENE-RA-TIN-GPLA   |
| Connection Style:  |
| Swivel nut, inverted flare 2nd end   |
| End Connection Design:   |
| Straight 2nd end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Burst Test Pressure:   |
| 23000.0 pounds per square inch   |
| Layer Composition And Location:  |
| 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure:  |
| 5800.0 pounds per square inch  |
| Thread Size:   |
| 0.438 inches 1st end   |
| Seat Angle:  |
| 37.0 degrees 1st end   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 50.0 feet excluding end fittings   |
| Product Name:  |
| Reel, hose   |
| Special Features:  |

Assembly includes one male 1/4"mpt and one female 1/4" swivel fitting on ends of hose

## NSN 4720-01-479-0581

Nonmetallic Hose Assembly - Page 2 of 2



| Media | For | Which | Desi | igned | ! |
|-------|-----|-------|------|-------|---|
|-------|-----|-------|------|-------|---|

Grease single response

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0