

View Online at <https://aerobasegroup.com/nsn/4720-01-479-1507>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

Between 1.125 inches and 1.172 inches

**Temperature Rating:**

-55.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

**Outside Diameter:**

Between 1.456 inches and 1.518 inches

**Minimum Inside Bending Radius:**

4.500 inches

**Hose Or Tubing Specification/std Data:**

Mil-h-13444e, type iii standard (includes industry or association standards, individual manufactureer standards, etc.).

**First End Fitting Specification/std Data:**

Sae j516, type 4a-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

**End Application:**

FAMI-LY-OFM-EDIU

**Connection Style:**

Swivel nut, inverted flare 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting zinc 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

1250.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer molded rubber, synthetic err-100

**Maximum Operating Pressure:**

300.0 pounds per square inch

**Thread Size:**

1.312 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

3848.1 millimeters and 3873.5 millimeters

**Product Name:**

Hose assembly, transmission cooler inlet

**Special Features:**

152" hose assembly with two straight 1" female connections

**Media For Which Designed:**

Oil, lubricating, diester base single response

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-13444 spec.