NSN 4720-01-479-3482

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-479-3482

| Round |
|---|
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| Between 0.875 inches and 0.917 inches |
| Tempurature Rating: |
| -55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response |
| Outside Diameter: |
| Between 1.175 inches and 1.237 inches |
| Minimum Inside Bending Radius: |
| 3.500 inches |
| End Application: |
| Family of medium tactical vehicles medium |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Burst Test Pressure: |
| 1500.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided fabric and 2nd layer braided wire |
| Maximum Operating Pressure: |
| 375.0 pounds per square inch |
| Thread Size: |
| 1.062 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 750.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 2006.3 millimeters and 2031.7 millimeters |
| Product Name: |

Hose assembly, transmission cooler

NSN 4720-01-479-3482

Nonmetallic Hose Assembly - Page 2 of 2



| Media For Which Designe | Which Designe | ed |
|-------------------------|---------------|----|
|-------------------------|---------------|----|

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0