## NSN 4720-01-479-7886

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-479-7886

Cross Sectional Snape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.875 inches and 0.917 inches
Tempurature Rating:
-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
Between 1.175 inches and 1.237 inches
Minimum Inside Bending Radius:
3.500 inches
End Application:
Family of medium tactical vehicles medium
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
1500.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and 2nd layer braided wire
Maximum Operating Pressure:
375.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
750.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
1487.3 millimeters and 1512.7 millimeters
Product Name:

Hose assembly, transmission cooler

## NSN 4720-01-479-7886

Nonmetallic Hose Assembly - Page 2 of 2



Media	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Un 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0