NSN 4720-01-480-6779

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-480-6779

Cross Sectional Shape:

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.562 inches
Minimum Inside Bending Radius:
4.625 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant and fuel resistant
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
6.250 inches working
Thread Series Designator:

Unjf 1st end

NSN 4720-01-480-6779

Nonmetallic Hose Assembly - Page 2 of 2



Spec	cific	ation	Data:
------	-------	-------	-------

81349-mil-h-25579c government specification

Specification Or Standard:

1 class and 8 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0