

View Online at <https://aerobasegroup.com/nsn/4720-01-480-9173>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

275.0 degrees fahrenheit single response

Outside Diameter:

0.625 inches

Minimum Inside Bending Radius:

5.500 inches

End Application:

Sea king helicopter

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

5500.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.875 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

27.750 inches working

Special Features:

Assembly has removeable hose ends; straight end passivate cres and anodize aluminum; elbow end do not passivate cres and anodize aluminum with blue dye; material cres class 304, condition a, qq-s-763; straight end aluminum alloy 6061-t651 qq-a-225/8; elbow end aluminum alloy 2024,qq-a-225

Media For Which Designed:

Fuel/oil, hydrocarbon single response and air single response and hydraulic fluid single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0