

View Online at <https://aerobasegroup.com/nsn/4720-01-480-9557>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.406 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

0.585 inches

Minimum Inside Bending Radius:

4.625 inches

Exterior Color:

Natural

End Application:

Carrier, bridge launcher; tank, m1 abrahms

Connection Style:

Swivel nut, flareless 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

8000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.750 inches 2nd end

Seat Angle:

12.0 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Vacuum In Torr:

28.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

25.750 inches

Special Features:

Sleeve per as1073, abrasion protection, heat shrinkable, black polyolefin; temp range minus 65 degrees through 25 degrees f

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms8001c government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0