NSN 4720-01-481-2257

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-481-2257

Between 0.391 inches and 0.421 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
Between 0.546 inches and 0.585 inches
Minimum Inside Bending Radius:
4.625 inches
End Application:
TANK-,A-BRA-MSM1
Connection Style:
Swivel nut, inverted flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Seat Angle:
24.0 degrees 2nd end
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
25.750 inches
Special Features:
Hose assembly has one straight fitting and one 90 degree fitting at 25-3/4in long per ms8006b
Thread Series Designator:
Unjf 1st end

NSN 4720-01-481-2257

Nonmetallic Hose Assembly - Page 2 of 2



S	pec	ific	cati	on	Data:

96906-ms8006b government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0