Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-481-6669

Cross Se	ectional Shape:
Round	
Thread C	lass:
3b 1st en	d
Thread D	Direction:
Right-han	nd 1st end
Inside Di	ameter:
0.188 incl	hes
Tempura	ture Rating:
-65.0 deg	rees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside I	Diameter:
0.250 incl	hes
Minimum	n Inside Bending Radius:
2.000 incl	hes
Connecti	ion Style:
Swivel nu	it, flareless 2nd end
End Con	nection Design:
Straight 1	st end
Connecti	ion Type:
Threaded	I internal tube 1st end
Burst Te	st Pressure:
12000.0 p	bounds per square inch
Layer Co	omposition And Location:
Outer laye	er braided corrosion resistant steel wire
Maximun	n Operating Pressure:
1500.0 pc	ounds per square inch
Thread S	ize:
0.438 incl	hes 1st end
Seat Ang	jle:
12.0 degr	rees 2nd end
Flow Ang	gle:
90.0 degr	rees 2nd end
Inside Su	urface Condition:
Smooth	
Measurin	ng Method And Length:
11.000 in	ches working
Thread S	Series Designator:
Unf 2nd e	and
Specifica	ation Data:
96906-ms	s8006 government standard
Shelf Life	9:
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0