

View Online at <https://aerobasegroup.com/nsn/4720-01-481-7627>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-29.0 degrees fahrenheit single response and 257.0 degrees fahrenheit single response

Outside Diameter:

0.500 inches

Hose Or Tubing Specification/std Data:

Sae j30r7-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Application:

FAMI-LY-OFM-EDIU

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

250.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer rubber impregnated fabric

Maximum Operating Pressure:

50.0 pounds per square inch

Thread Size:

0.313 inches 1st end

Seat Angle:

37.0 degrees 1st end

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

108.000 inches excluding end fittings

Second End Swivel Action Capability:

Not included

Product Name:

Hose assembly, pump discharge

Special Features:

Includes 2ea p/n 30682-5-4 or equal; 2ea clamps p/n hc9-8 or equal; 1ea hose p/n 293-5 or equal (sae j30r7); 1ea elbow p/n sae 514 5-4-070202

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Specification Data:

Sae j30r7-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0