## NSN 4720-01-482-3637

Air Duct Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-482-3637

| Cross Sectional Shape:  |
|---|
| Round   |
| Wall Thickness:   |
| 0.220 inches  |
| Inside Diameter:  |
| 2.250 inches first end  |
| Minimum Inside Bending Radius:  |
| 1.125 inches  |
| Vacuum Rating:  |
| 10.0 inches of mercury  |
| End Application:  |
|   |
| Armored airborne reconnaissance assault vehicle; bfvs                                   |
| Connection Type: Plain both ends  |
| Features Provided:  |
| Fungus resistant treatment and ozone resistant  |
| Maximum Operating Pressure:   |
| 16.0 pounds per square inch   |
| Product Name:   |
| Hose, air duct, high temp, flexible, reinforced   |
| External Operating Pressure:  |
|   |
| 5.0 pounds per square inch  Material:   |
| Steel reinforcing wire  |
| Material Specification:   |
| Mil-prf-62028c, type ii, class3 military specification all material responses all plies |
| Style Designator:   |
| Helically wound continous wire supported  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| Unit Of Weasure.  |
| Demilitarization:   |
| Yes - demil/mli   |
|   |
| <b>Fiig:</b> A229a0   |
|   |
| Mil-std (military Standard):  |
| Mil-prf-62028c spec.  |