NSN 4720-01-482-5562

Cross Sectional Shape:

for tube size specified

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-482-5562

Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.250 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response				
Outside Diameter:				
0.420 inches				
Minimum Inside Bending Radius:				
0.620 inches				
Exterior Color:				
Green				
End Application:				
F/a-18, hornet				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Burst Test Pressure:				
500.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided corrosion resistant steel wire and outer layer rubber impregnated braided fabric				
Maximum Operating Pressure:				
125.0 pounds per square inch				
Thread Size:				
0.438 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
250.0 pounds per square inch				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
23.000 inches working				
Special Features:				

Hose assembly internal springwire ends shall be attached to nipple; assembly is rated at low pressure; end fittings to mate with sae-as4395

NSN 4720-01-482-5562

Nonmetallic Hose Assembly - Page 2 of 2



Th.		Carias	Dania	
1111	reau	Series	Desig	mator.

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0