## NSN 4720-01-482-5573

**Cross Sectional Shape:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-482-5573

Round						
Thread Class:						
3b 1st end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.375 inches						
Tempurature Rating:						
-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response						
Outside Diameter:						
0.590 inches						
Minimum Inside Bending Radius:						
0.870 inches						
Exterior Color:						
Green						
End Application:						
F/a-18, hornet						
Connection Style:						
Swivel nut flare 1st end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Burst Test Pressure:						
500.0 pounds per square inch						
Layer Composition And Location:						
1st layer braided corrosion resistant steel wire and outer layer rubber impregnated braided fabric						
Maximum Operating Pressure:						
125.0 pounds per square inch						
Thread Size:						
0.562 inches 1st end						
Seat Angle:						
37.0 degrees 1st end						
Hydrostatic Test Pressure:						
250.0 pounds per square inch						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
23.000 inches working						
Special Features:						

Hose assembly internal springwire ends shall be attached to nipple; assembly is rated at low pressure; end fittings to mate with sae-as4395 for tube size specified

## NSN 4720-01-482-5573

Nonmetallic Hose Assembly - Page 2 of 2



	••		•	_		
ı	hre	ลด	Seri	26 I I	PSIU	nator:
•		uu	CCII		COIG	mator.

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0