

View Online at <https://aerobasegroup.com/nsn/4720-01-482-9893>

**Cross Sectional Shape:**

Round

**Thread Class:**

3a 1st end

**Inside Diameter:**

1.500 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

2.000 inches

**Minimum Inside Bending Radius:**

5.000 inches

**Exterior Color:**

Black or green or blue

**End Application:**

Hydraulic power unit

**Thready Qty Per Inch (tpi):**

12 1st end

**Burst Test Pressure:**

15000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire and 2nd layer spirally wrapped corrosion resistant steel fabric and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

5000.0 pounds per square inch

**Thread Size:**

3.060 inches 1st end

**Hydrostatic Test Pressure:**

10000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant and oxidation resistant and light resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

66.140 inches random

**Special Features:**

Uses band-type segmented fittings not screw-type fittings

**Media For Which Designed:**

Fuel/oil, hydrocarbon and hydraulic fluid, phosphate-ester base single response

**Thread Series Designator:**

Un 1st end

**Specification Data:**

81349-mil-h-24135/ (sh) government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0