

View Online at <https://aerobasegroup.com/nsn/4720-01-483-0268>

Cross Sectional Shape:

Round

Thread Class:

3a 1st end

Inside Diameter:

1.500 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

2.000 inches

Minimum Inside Bending Radius:

5.000 inches

Exterior Color:

Black or green or blue

End Application:

Hydraulic power unit

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

15000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and 2nd layer spirally wrapped corrosion resistant steel fabric and outer layer molded rubber, synthetic

Maximum Operating Pressure:

5000.0 pounds per square inch

Thread Size:

3.060 inches 1st end

Hydrostatic Test Pressure:

10000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and oxidation resistant and light resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

56.460 inches random

Special Features:

Uses band-type segmented fittings not screw-together fittings

Media For Which Designed:

Fuel/oil, hydrocarbon and hydraulic fluid, phosphate-ester base single response

Thread Series Designator:

Un 1st end

Specification Data:

81349-mil-h-24135/ (sh) government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0