NSN 4720-01-484-3584



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-484-3584 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.000 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 1.953 inches **Minimum Inside Bending Radius:** 5.500 inches **End Application:** Helicopter, sea knight model ch-46 **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Elbow 2nd end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end **Burst Test Pressure:** 600.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyester cord and outer layer braided polyester cord **Maximum Operating Pressure:** 100.0 pounds per square inch **Thread Size:** 1.3125 inches 1st end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 300.0 pounds per square inch Flow Angle: 90.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

22.500 inches working

NSN 4720-01-484-3584

Nonmetallic Hose Assembly - Page 2 of 2



P	r۸	d	ct	N	а	m	ρ

Hose assembly, rubber, medium pressure crimped adapter assembly, flared, 90 degree adapter assembly, flared, 45 degrees

Special Features:

Self sealing crash resistant fuel hose

Thread Series Designator:

Unj 2nd end

o.., =....

Shelf Life:

Unit Of Measure:

__

N/a

Demilitarization:

No

Fiig:

A542a0