

View Online at <https://aerobasegroup.com/nsn/4720-01-484-3584>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.000 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

1.953 inches

Minimum Inside Bending Radius:

5.500 inches

End Application:

Helicopter, sea knight model ch-46

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

600.0 pounds per square inch

Layer Composition And Location:

1st layer braided polyester cord and outer layer braided polyester cord

Maximum Operating Pressure:

100.0 pounds per square inch

Thread Size:

1.3125 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

300.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

22.500 inches working

Product Name:

Hose assembly, rubber, medium pressure crimped adapter assembly, flared, 90 degree adapter assembly, flared, 45 degrees

Special Features:

Self sealing crash resistant fuel hose

Thread Series Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0