NSN 4720-01-484-7276

Cross Sectional Shape:

Round

Thread Class: 2b 1st end

Thread Direction:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-484-7276

Right-hand 1st end
Inside Diameter:
Between 0.250 inches and 0.273 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response
Outside Diameter:
0.619 inches
Minimum Inside Bending Radius:
4.000 inches
End Application:
NHA1-23-648-20;M
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
20000.0 pounds per square inch
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.4375 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
10000.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
21.000 inches working
Product Name:
Hose assembly
Media For Which Designed:
Hydraulic fluid single response and hydraulic fluid, water base single response

NSN 4720-01-484-7276

Nonmetallic Hose Assembly - Page 2 of 2



Ihread	Series	Designator:
Unf 1st	end	

N/a

Shelf Life:

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0