## NSN 4720-01-484-7276

**Cross Sectional Shape:** 

Round

Thread Class: 2b 1st end

**Thread Direction:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-484-7276

| Right-hand 1st end  |
|---|
| Inside Diameter:  |
| Between 0.250 inches and 0.273 inches   |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.619 inches  |
| Minimum Inside Bending Radius:  |
| 4.000 inches  |
| End Application:  |
| NHA1-23-648-20;M  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 20000.0 pounds per square inch  |
| Maximum Operating Pressure:   |
| 5000.0 pounds per square inch   |
| Thread Size:  |
| 0.4375 inches 1st end   |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 10000.0 pounds per square inch  |
| Outer Covering Environmental Protection:  |
| Oil resistant and weatherproof  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 21.000 inches working   |
| Product Name:   |
| Hose assembly   |
| Media For Which Designed:   |
| Hydraulic fluid single response and hydraulic fluid, water base single response       |

## NSN 4720-01-484-7276

Nonmetallic Hose Assembly - Page 2 of 2



| Ihread  | Series | Designator: |
|---------|--------|-------------|
| Unf 1st | end    |             |

N/a

Shelf Life:

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0