

View Online at <https://aerobasegroup.com/nsn/4720-01-485-1943>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Temperature Rating:

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:

1.030 inches

Minimum Inside Bending Radius:

7.000 inches

End Application:

Recovery vehicle, full tracked m88a2, nsn 2350-01-390-4683; nha winch hoist p/n 12364666

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

1400.0 pounds per square inch

Layer Composition And Location:

2nd layer braided textile yarn and outer layer braided polyester cord

Maximum Operating Pressure:

350.0 pounds per square inch

Thread Size:

1.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

42.870 inches

Special Features:

Hose assembly only has one fitting attached; hose p/n fc466-12, and fitting p/n 1ga16fj12, aeroquip parts per source control drawing 12366363

Media For Which Designed:

Fuel/oil, hydrocarbon and water single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0