NSN 4720-01-485-4072

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-485-4072

| Thread Class: |
|---|
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.406 inches |
| Tempurature Rating: |
| -54.0 degrees celsius single response and 149.0 degrees celsius single response |
| Outside Diameter: |
| 1.020 inches |
| Minimum Inside Bending Radius: |
| 4.620 inches |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 16 2nd end |
| Burst Test Pressure: |
| 8000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 3000.0 pounds per square inch |
| Flow Angle: |
| 45.0 degrees 2nd end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 21.750 inches working |
| Media For Which Designed: |
| Hydraulic fluid single response and fuel/oil, hydrocarbon single response |

NSN 4720-01-485-4072

Nonmetallic Hose Assembly - Page 2 of 2



| Thread | Series | Design | nator: |
|--------|--------|--------|--------|
| | 0000 | -00.9. | |

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0