

View Online at <https://aerobasegroup.com/nsn/4720-01-485-7956>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.625 inches

Temperature Rating:

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:

1.125 inches

Minimum Inside Bending Radius:

8.000 inches

End Application:

2320-02-443-8023, 2320-01-442-1940, truck, cbt, (command bridge transporter)

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

11000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

2750.0 pounds per square inch

Thread Size:

0.875 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Oil resistant and water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

58.000 inches

Special Features:

Hose is sae 100r2at-10, 1 ea fitting-sae 10-10 240354ca, 1 ea fitting-sae 10-10 240154ca

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0