

View Online at <https://aerobasegroup.com/nsn/4720-01-485-7963>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.625 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

**Outside Diameter:**

1.125 inches

**Minimum Inside Bending Radius:**

8.000 inches

**End Application:**

2320-02-443-8023, 2320-01-442-1940, truck, cbt, (command bridge transporter)

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

11000.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided steel wire and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

2750.0 pounds per square inch

**Thread Size:**

0.875 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Oil resistant and water resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

88.000 inches

**Special Features:**

Hose is sae 100r2at-10, 1 ea fitting-sae 10-10 240254ca, 1 ea fitting-sae 10-10 240154ca

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0