NSN 4720-01-485-8125

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-485-8125

Cross Sectional Shape:
Round
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
1.420 inches
Minimum Inside Bending Radius:
10.000 inches
Exterior Color:
Black
Quick Disconnect Size:
1.000 inches 2nd end
End Application:
ALLS-OU-RCE-ANAL
Connection Style:
Cam or lever (external) 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Internal quick disconnect 1st end
Burst Test Pressure:
800.0 pounds per square inch
Layer Composition And Location:
1st layer braided synthetic cord and 2nd layer braided synthetic cord and outer layer molded rubber, ethylene propylene
Maximum Operating Pressure:
200.0 pounds per square inch
Outer Covering Environmental Protection:
Heat resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
28.620 inches
Special Features:
Assembly also consists of 4 ea hose clamps, commerical grade (worm screw type)
Media For Which Designed:
Water single response
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4720-01-485-8125

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0