## NSN 4720-01-486-0164

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-486-0164 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 140.0 degrees fahrenheit single response **Outside Diameter:** 0.540 inches **Minimum Inside Bending Radius:** 3.500 inches **Connection Style:** Nut assembly with gasket 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal hose 2nd end **Burst Test Pressure:** 41000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and outer layer molded polyurethane **Maximum Operating Pressure:** 16400.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 58.0 degrees 2nd end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 86.000 inches working **Product Name:** Polyflex hose assembly **Special Features:** Hose assembly with 2300 series hose and type m swivel nut hose fittings, cone seat angle 58 degrees **Thread Series Designator:** Unf 1st end

N/a

Shelf Life:

## NSN 4720-01-486-0164

Nonmetallic Hose Assembly - Page 2 of 2



| ш | ın | 10 | <i>(</i> )+ | Measure: |  |
|---|----|----|-------------|----------|--|
|   |    |    |             |          |  |

--

Demilitarization:

No

Fiig:

A542a0