## NSN 4720-01-486-1438

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-486-1438 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.760 inches **Minimum Inside Bending Radius:** 1.500 inches **End Application:** Arleigh burke class ddg, nha generator set ag9140rf **Connection Style:** Swivel nut, gasket seal 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:** 0.812 inches 1st end **Inside Surface Condition:** Convoluted **Measuring Method And Length:** 31.000 inches **Special Features:** Hose is conductive ptfe lined fibergless reinforced innercore, overbraided with 300 series stainless steel **Thread Series Designator:** 

Un 1st end

Shelf Life:

N/a

## NSN 4720-01-486-1438

Nonmetallic Hose Assembly - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A542a0