NSN 4720-01-486-1556

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.313 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-486-1556

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:
0.446 inches
Minimum Inside Bending Radius:
4.000 inches
End Application:
Arleigh burke class ddg; nha generator set ag9140rf
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
6500.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
180.000 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response and hydraulic fluid single response
Thread Series Designator:
Unjf 1st end
Specification Data:
96906-ms8005c government specification

NSN 4720-01-486-1556

Nonmetallic Hose Assembly - Page 2 of 2



_			-		
C	hο	14		.ife	•
•			_	.II C	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0