NSN 4720-01-486-4275

Cross Sectional Shape:

Inside Diameter: 1.026 inches

Tempurature Rating:

Bolt Circle Diameter: 1.230 inches 2nd end

Round

20.0

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-486-4275

-65.0 degrees fahrenheit single response and 265.0 degrees fahrenheit single response

Flange Thickness:
0.675 inches 2nd end
Outside Diameter:
Between 1.250 inches and 1.560 inches
Minimum Inside Bending Radius:
4.500 inches
Bolt Hole Quantity:
5 2nd end
Flange Outside Diameter:
1.743 inches 2nd end
End Application:
Environmental control system coolant line
Bolt Hole Diameter:
0.035 inches 1st end and 0.040 inches 1st end
End Flange Construction:
Solid 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Plain face flange 2nd end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
475.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
190.0 pounds per square inch
Hydrostatic Test Pressure:
285.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Vacuum In Torr:

NSN 4720-01-486-4275

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
18.000 inches working
Flange Style:
Round w/ bolt holes 2nd end
Special Features:
$Ferrule, swage, tube \ couplings \ on \ both \ ends, \ threaded \ external \ 1 \ 3/4-12un-2a, \ slotted, \ p/n \ w83051-20$
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0