Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-487-1445

C1055 3eci	ional Shape:
Round	
Thread Dir	ection:
Right-hand	1st end
Inside Diar	neter:
0.380 inche	S
Tempuratu	re Rating:
-40.0 degre	es celsius and 100.0 degrees celsius single response
Outside Di	ameter:
0.570 inche	S
Minimum I	nside Bending Radius:
2.000 inche	S
End Applic	ation:
Nssn class	submarine; nha: lpt and wst 30 inch lower hatch-dwg no. 7066805
Connectio	n Style:
External se	at for gasket seal (boss) 1st end
End Conne	ection Design:
Straight 1st	end
Connectio	п Туре:
Threaded e	xternal pipe 1st end
Layer Com	position And Location:
2nd layer b	raided steel wire and outer layer molded rubber, synthetic
Maximum	Operating Pressure:
4000.0 pou	nds per square inch
Thread Siz	e:
0.375 inche	s 1st end
Inside Surf	ace Condition:
Smooth	
Measuring	Method And Length:
20.0 feet	
Special Fea	atures:
Heavy duty	rubber hose (900-series), flexible with little "memory", is the best choice for long hose runs
Media For	Which Designed:
Fuel/oil, hy	drocarbon single response
Thread Ser	ies Designator:
Npt 1st end	
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitariz	ation:
No	

NSN 4720-01-487-1445

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

