NSN 4720-01-487-6930

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches

Outside Diameter:

0.375 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-487-6930

Angle Between Rigid Elbow Fittings In Deg:
45.0
End Application:
Engine, aircraft, j85-ge-5/13 (f-5a/b, t-38a)
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
20 2nd end
Burst Test Pressure:
10000.0 pounds per square inch
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.500 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
21.375 inches excluding end fittings
Product Name:
Hose-med. Pressure polytetrafluoroethylene 90 degrees to 45 degrees end fittings

NSN 4720-01-487-6930

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:
Similar to r1023c213a045
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0