## NSN 4720-01-491-7423

Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-491-7423

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.875 inches and 0.917 inches
Tempurature Rating:
-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
Between 1.175 inches and 1.237 inches
Minimum Inside Bending Radius:
7.380 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
1500.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
375.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
750.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
38.000 inches
Media For Which Designed:

## NSN 4720-01-491-7423

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Des	ignator:
Un 1st	end		

.....

Shelf Life:

Unit Of Measure:

-

N/a

Demilitarization:

No

Fiig:

A542a0