

View Online at <https://aerobasegroup.com/nsn/4720-01-491-9442>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

12.7 millimeters

Temperature Rating:

-55.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

Outside Diameter:

Between 20.52 millimeters and 21.69 millimeters

Minimum Inside Bending Radius:

2.250 inches

End Application:

FMTV-;2-320-0144

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

3500.0 pounds per square inch

Maximum Operating Pressure:

875.0 pounds per square inch

Thread Size:

0.750 inches 2nd end

Seat Angle:

45.0 degrees 2nd end

Hydrostatic Test Pressure:

1750.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

984.6 millimeters working and 1002.6 millimeters working

Product Name:

Hose assembly, ctis inflate, lh and rh

Special Features:

Critical safety item; driver side inflate

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A542a0