

View Online at <https://aerobasegroup.com/nsn/4720-01-491-9442>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

12.7 millimeters

**Temperature Rating:**

-55.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

**Outside Diameter:**

Between 20.52 millimeters and 21.69 millimeters

**Minimum Inside Bending Radius:**

2.250 inches

**End Application:**

FMTV-;2-320-0144

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

3500.0 pounds per square inch

**Maximum Operating Pressure:**

875.0 pounds per square inch

**Thread Size:**

0.750 inches 2nd end

**Seat Angle:**

45.0 degrees 2nd end

**Hydrostatic Test Pressure:**

1750.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

984.6 millimeters working and 1002.6 millimeters working

**Product Name:**

Hose assembly, ctis inflate, lh and rh

**Special Features:**

Critical safety item; driver side inflate

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A542a0