

View Online at <https://aerobasegroup.com/nsn/4720-01-492-2708>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

Outside Diameter:

1.156 inches

Minimum Inside Bending Radius:

5.500 inches

Angle Between Rigid Elbow Fittings In Deg:

30.0

End Application:

Used on high pressure aircraft hydraulic landing gear systems

Connection Style:

Swivel nut, flareless 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

2500.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire

Maximum Operating Pressure:

625.0 pounds per square inch

Thread Size:

1.313 inches 2nd end

Seat Angle:

12.0 degrees 2nd end

Hydrostatic Test Pressure:

1500.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

12.625 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A542a0