NSN 4720-01-492-3841

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-492-3841

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.212 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.515 inches
Minimum Inside Bending Radius:
1.500 inches
Exterior Color:
Black or yellow
End Application:
Used on high pressure aircraft hydraulic landing gear systems
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Connection Type: Threaded internal tube 1st end
Threaded internal tube 1st end
Threaded internal tube 1st end Burst Test Pressure:
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location:
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire Maximum Operating Pressure:
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size:
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle:
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Flow Angle:
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Flow Angle: 90.0 degrees 1st end
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Flow Angle: 90.0 degrees 1st end Inside Surface Condition:
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth
Threaded internal tube 1st end Burst Test Pressure: 16000.0 pounds per square inch Layer Composition And Location: 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length:

NSN 4720-01-492-3841

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	-00.9.	

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0