

View Online at <https://aerobasegroup.com/nsn/4720-01-492-5003>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

15.875 millimeters

Temperature Rating:

-55.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

Outside Diameter:

Between 23.6982 millimeters and 24.8666 millimeters

Minimum Inside Bending Radius:

69.85 millimeters

End Application:

MEDI-UM-TAC-TICA

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

3000.0 pounds per square inch

Maximum Operating Pressure:

750.0 pounds per square inch

Thread Size:

0.875 inches 2nd end

Seat Angle:

45.0 degrees 2nd end

Hydrostatic Test Pressure:

1500.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Oil resistant and heat resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

888.8 millimeters working

Product Name:

Hose assembly, hub vent, fron lh

Special Features:

Includes first end fitting 10-10 301447, second end 10-10 300147

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0